

M2M Customized Room Parameter Data Logging & Live Alerting System

Model
IBI-MC-X



IBI-MC-X

4G LTE CAT1 Technology with In-built M2M SIM



Specifications

IBI-MC-X M2M Customized Room Parameter Data Logging & Live Alerting System

Device Type

Digital Data Logger

Description

4G M2M Customized Data Logger - Sensor & Accessories need to be procure separately

Hardware Features

- 1.3" 128X64 OLED monochrome Graphical Display
- Internal Li-Ion 4000 mAh battery with under/over voltage protection, up to 20 Hrs battery back-up during power failure
- Plug & Play, Wall Mountable Device
- Polling Data Interval 15 minutes (default), Configurable
- Internal Storage of 90 days at sampling frequency of 15 mins
- DC Input Voltage 5V/1A
- IP64 Rated Enclosure

Software Features

- Different Views (Dashboard / Map / List), Analytics, Device Management, User Management, Alerts Management
- Custom Reports (21CFR Part 11 Compliant) PDF
- MKT Value, Audit Trail, Alarm Log, Trend Graphs
- Data Polling Interval: 15 minutes (default) - User configurable
- SMS: Optional
- Alerts & Push Notifications
- Web & Mobile App (iOS & Android)



www.ideabytesiot.com

vinay.bandela@ideabytes.com

Call: 1800 571 5566

Ideabytes Software India Pvt Ltd, 2nd Floor, Kapil Towers, Financial District,
Nanakaramguda, Hyderabad-500032, Telangana, India.