Wi-Fi/4G M2M SIM Data Logger for **Temperature & Humidity Live** Monitoring with Mobile App, **Alerts & Analytics**

Model **IBI-WTH50 IBI-MTH50**











IBI-MTH50 4G LTE CAT1 Technology with In-built M2M SIM





Specifications

Temperature & Humidity Data Logger

Device Type	Temperature & Humidity
Temperature Range	0°C to +50°C
Accuracy	± 0.5°C (0°C to +50°C)
Resolution	0.1°C
Humidity Range	0 to 100% RH
Accuracy	± 2% RH
Resolution	0.1% RH

Hardware Features

- 1.3" 128X64 OLED monochrome Graphical Display
- Internal Li-Ion 4000 mAh battery with under/over voltage protection, up to 20 Hrs battery back-up during power failure
- Plug & Play, Wall Mountable Device
- Polling Data Interval 15 minutes (default), Configurable
- Internal Storage of 100 days at sampling frequency of 15 mins
- DC Input Voltage 5V/1A
- IP64 Rated Enclosure

Software Features

- Different Views (Dashboard / Map / List), Analytics, Device Management, User Management, Alerts Management
- Custom Reports (21CFR Part 11 Compliant) PDF, CSV
- MKT Value, Audit Trail, Alarm Log, Trend Graphs
- Data Polling Interval: 15 minutes (default) User configurable
- SMS: Optional
- Alerts & Push Notifications
- Web & Mobile App (iOS & Android)













Power Adapter







www.ideabytesiot.com vinay.bandela@ideabytes.com

Call: 1800 571 5566